Pinnacle™ PA-60 Accent Light



PROJECT NAME

TYPE

CATALOG #

QUANTITY


NOTES



Pairing up-and-down lighting capabilities with a watertight design, the PA-60 delivers limitless versatility and lasting performance for any application.

Quick Facts

- Infinity Screw design allows continuous 360° adjustment to fine-tune light direction, even after installation
- Premium brass construction with optional copper shroud provides maximum durability
- IP66- and IP67-rated for protection against water intrusion
- PowerBoard® Integrated LEDs offer Luxor® compatibility for smooth dimming and RGBW color-changing control options

PA-60 Photometric Chart



PA-60 Spec Chart

Light Source	6LED	9LED	ZDC
Total Lumens (lm)	532	707	120-375
Power Consumption (VA)	9.3 VA	12.2 VA	11.0 VA
Efficacy (lm/W)	71	63	23
Correlated Color Temperature (CCT)	2700K	2700K	RGBW
Beam Angle	35°	35°	50°
Maximum Candela (cd)	1,129	1,572	196
Color Rendering Index (CRI)	83	83	80+
Input Voltage (V)	7.7 W	11.1 W	9.1 W
Minimum Rated Life (L70)	72,000 Hrs	72,000 Hrs	55,000 Hrs

Technical Specifications

About FX Luminaire

As a leading manufacturer of landscape and architectural lighting, FX Luminaire provides innovative products, resources, and support to help customers bring their visions to life. The company offers a range of specification-driven solutions, including fixtures, controls, and accessories, to enhance residential and commercial landscapes.

CONSTRUCTION

Materials	Machined C360 brass housing, shroud, and knuckle with brass hardware
Threads	½"–14 (13 mm) NPSM threads
Adjustability	Adjustable knuckle with ProAim® Technology
Finish	Options of natural brass finish, or antiqued finish with brushed (Antique Bronze) effect. Antique finish sealed with a clear TGIC powder-coated layer and polyester TGIC powder-coated finish provides superior outdoor weathering in all conditions. Tested to ASTM standards.
Hardware	Brass angle lock screw
Wiring	18 AWG (1 mm); SPT-1W; 220°F (105°C); 300 V; 10' (3 m) length
Sockets	Socket contains MoistureBlock™ Technology to prevent moisture from wicking up into sealed areas of the fixture.
Glare Control	Machined brass shroud with straight (standard) or 45° long shroud option
Weight	4.8 lb (2.2 kg)
Ambient Operating Temperature	0°F to 140°F (-18°C to 60°C)
Lens Transparency	Clear (ZD) or frosted (ZDC)

SUSTAINABILITY & MANUFACTURING

Installation Requirements	Designed for installation in up or down orientations.
Manufacturing	9001:2015 ISO certified facility
Lifetime	L70 rating conforms to IES LM-80/TM-21 standards, projecting lumen maintenance to 70% of initial output.
Warranty	10-year warranty

LISTINGS

ADDITIONAL CERTIFICATIONS

UL 1838

Model Configurator

PA60					
MODEL	LUXOR CONTROL	POWER	LED COLOR	GLARE CONTROL	FINISH

LUXOR CONTROL

- ☐ **ZD** — Zone/Dim with Luxor
- ☐ **ZDC** — Zone/Dim/Color with Luxor

POWER

- ☐ **6LED** — 9.3 VA Per Aperture
- ☐ **9LED** — 12.2 VA
- ☐ **[Default]** — 11 VA, 110-260 lm, ZDC Option Required

LED COLOR

- ☐ **[Default]** — Default ZDC option 11.0 VA
- ☐ **W** — Warm (2700K)
- ☐ **S** — Soft (3000K)
- ☐ **C** — Cool (4000K)

GLARE CONTROL

- ☐ **[Default]** — Straight Cut Shroud
- ☐ **LS** — 45° Angled Long Shroud

FINISH

- ☐ **AB** Antique Bronze
- ☐ **BS** Natural Brass
- ☐ **BZ** Bronze Metallic
- ☐ **FB** Black
- ☐ **CU** Natural Copper

Accessories

MOUNTING

- ☐  **PM-XX*** PM
  Post Mount
- ☐  **GM-XX*** GM
  Ground Mount with ½" Thread
- ☐  **VB-050-XX*** VB-050
  VersaBox® Mount with ½" Thread
- ☐  **MJB-050-XX*** MJB-050
  Mini J-Box for ½" Thread
- ☐  **753900**
  Super Slot Spike
- ☐  **250015840000**
  Long Slot Spike
- ☐  **250020020000**
  Three-Prong Spike
- ☐  **VHR-UL** VHRUL
  Variable Height Riser for Up Lights
- ☐  **SJ-XX*** SJ
  Super J-Box Spike
- ☐  **YY*-R-GT-XX***
  1.0" (25 mm) Copper Riser for GT Path Light
- ☐  **PARS**
  ProAim® Ratcheting Spike

POWER

- ☐  **MT-6W**
  Plug-In Transformer, 6 W
- ☐  **ST-UV**
  Step-Down Transformer, UV (120/277 V to 12 V)
- ☐  **SURGE-MOD**
  Surge Protection Module