PAR-36 Eco LED Lamp



PROJECT NAME

TYPE

CATALOG #

QUANTITY

NOTES

The versatile MR-11 and AR-11 Eco Lamps are ideal for low-output applications while the powerful PAR-36 Eco Lamp is perfect for high-output needs.

Quick Facts

- Durable, lightweight aluminum housing withstands any weather condition
- Compatibility with Luxor® Low-Voltage CUBE for zoning and dimming capabilities
- Two beam angle options for greater design flexibility
- Two color temperature options offer a warm (2,700K) or soft (3,000K) look
- Available in 6 W and 10 W intensities for use in a variety of applications
- Comes preinstalled in CF Well Lights

PAR-36 Specification Chart

Output	ECO35	ECO50
Total Lumens	670 - 680	850 - 860
Power Consumption (VA)	8.5 W	11.3 W
Efficacy (lm/W)	115	115
Maximum Candelas (cd)	749 to 1,138	849 to 1,521
Color Rendering Index (CRI)	84 to 85	83 to 85
Input Voltage	10 to 15 VAC	10 to 15 VAC
Input Power	6.0 W	10.0 W
Control	Phase-cut*	Phase-cut*
Rated Life (L70)	50,000	50,000

* For optimal performance, use a trailing-edge (reverse phase-cut) dimmer.

ADDITIONAL CERTIFICATIONS

RoHS COMPLIANT

Model Configurator

PAR36ECO				
MODEL	LIGHTING ENGINE	POWER	LED COLOR	OPTIC

LIGHTING ENGINE

- ☐ **PAR-36**

POWER

- ☐ **35** — 335-480 lumens; 5.4 VA
- ☐ **50** — 6.5 VA

LED COLOR

- ☐ **W** — Warm (2700K)
- ☐ **S** — Soft (3000K)

OPTIC

- ☐ **FL** — Flood (30°)
- ☐ **WF** — Wide Flood (60°)

Accessories

POWER

- ☐  **LCM-LV** — Luxor Cube - Low-Voltage
- ☐  **DIM-LV** — Low-Voltage Dimmer