Cora™ CA-73 Accent Light



PROJECT NAME

TYPE

CATALOG #

QUANTITY

NOTES

The high-output CA-73 Accent Light brings powerful PAR-36 outdoor accent lighting to the Cora Collect for illuminating large trees and architectural features.

Quick Facts

- Designed to illuminate large trees, architectural elements, and focal points
- Outperforms MR-16 fixtures with higher-output PAR-36 Lamp
- Includes glare-reducing Hex Baffle
- Provides more coverage with fewer fixtures
- Constructed from select brass for long-term durability
- Maintains a cohesive look with other Cora Collection fixtures for design consistency

CA-73 Specification Chart

Light Source	E9	E12
Total Lumens (lm)	640	800
Power Consumption (VA)	8.5 VA	11.3 VA
Efficacy (lm/W)	110	90
Correlated Color Temperature (CCT)	2700K, 3000K	2700K, 3000K
Beam Angle	35°	35°
Maximum Candela (cd)	1,075	1,330
Color Rendering Index (CRI)	85+	85+
Input Voltage (V)	10 to 15	10 to 15
Minimum Rated Life (L70)	50,000 hrs	50,000 hrs

Technical Specifications

About FX Luminaire

As a leading manufacturer of landscape and architectural lighting, FX Luminaire provides innovative products, resources, and support to help customers bring their visions to life. The company offers a range of specification-driven solutions, including fixtures, controls, and accessories, to enhance residential and commercial landscapes.

CONSTRUCTION

LED	E12

ADDITIONAL CERTIFICATIONS

UL 1838

Model Configurator

CA73						
MODEL	LAMP	LED COLOR	OPTIC	COMPLIANCE	WIRE LEAD	FINISH

LAMP

- ☐ **E12** — 11.3 VA PAR-36 Eco LED Lamp
- ☐ **E9** — 8.5 VA PAR-36 Eco LED Lamp
- ☐ **NL** — Lamp Not Included

LED COLOR

- ☐ **W** — Warm (2700K)
- ☐ **[Default]** — No Lamp
- ☐ **S** — Soft (3000K)

OPTIC

- ☐ **[Default]** NL Lamp
- ☐ **FL** Flood (30°)

COMPLIANCE

- ☐  **[Default]** North America (UL Listed)

WIRE LEAD

- ☐ **[Default]** 10' (3 m)
- ☐ **XL** 26' (8 m) Lead

FINISH

- ☐  **AB** Antique Bronze
- ☐  **FB** Black

Accessories

MOUNTING

- ☐  **PM-XX*** PM — Post Mount
- ☐  **GM-XX*** GM — Ground Mount with ½" Thread
- ☐  **VB-050-XX*** VB-050 — VersaBox® Mount with ½" Thread
- ☐  **MJB-050-XX*** MJB-050 — Mini J-Box for ½" Thread
- ☐  **250015840000** — Long Slot Spike
- ☐  **250020020000** — Three-Prong Spike
- ☐  **VHR-UL** VHRUL — Variable Height Riser for Up Lights
- ☐  **SJ-XX*** SJ — Super J-Box Spike
- ☐  **PARS** — ProAim® Ratcheting Spike
- ☐  **eKitSpike** — CE Certified Spike



250030410000SP
Lock Ring



BM-050-C-AB
Bracket Mount



RSR-S-125-XX*-R-MF-B-AB RSRS125MFBAB
1.25" (32MM) Select Brass Riser



LS6054
2.5'' Post Mount with Stabilizer

POWER



MT-6W
Plug-In Transformer, 6 W



ST-UV
Step-Down Transformer, UV (120/277 V to 12 V)



SURGE-MOD
Surge Protection Module



LCM-LV
Luxor Cube - Low-Voltage



ST-120-DIM
Step-Down Transformer, Dimmable (120 V to 12 V)



MT-30W
Mini Plug-In Transformer, 30 W

SPLICING



WCHSBS2
Brass Lug Wire Connectors, 2-pack



WCHSBS50
Brass Lug Wire Connectors, 50-item Bulk Pack



WCHSSM20
Heat Shrink Wire Connectors, 20-pack, Small



WCHSMD20
Heat Shrink Wire Connectors, 20-pack, Medium



WCHSTOOL
Ratcheting Crimper Tool