Pinnacle™ NR Accent Light



PROJECT NAME
TYPE
CATALOG #
QUANTITY
NOTES

The FR and larger NR fixtures combine the elegance and performance of precious metals with all the beam angles and other features of our PowerBoard® integrated LEDs.

Quick Facts

- Premium, corrosion-resistant copper and brass construction protects internal and external elements of the fixture
- Includes field-servicable beam angle lenses from Very Narrow to Wide Flood
- Features ProAim® adjustability with compress-and-lock features to prevent slip after installation and over 220° of vertical adjustability
- Sturdy ground stake and rotational Lock Ring included for maximum sercurity and adjustability
- Angled or straight glare-control options
- Driver on Board Technology layout for compact design and fewer components
- Built-in Luxor® Technology enables powerline zoning, smooth dimming, and RGBW color-changing with the Luxor Controller
- Available in static color and dynamic RGBW color-changing options

NR Spec Chart

NUMBER OF LEDS	1	3	6	9	ZDC
Halogen Lumen Output Equivalent	10 Watt	20 Watt	35 Watt	50 Watt	20 Watt
Minimum Rated Life (L70)	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg	50,000 hrs avg
Input Voltage	10 to 15V	10 to 15V	10 to 15V	10 to 15V	10 to 15V
VA Total (Use this number to size the transformer)	2.4	4.5	13.5	13.5	11.0
Watts Used	2.0	4.2	10.1	11.2	9.1
Efficacy (Lumens per Watt)	38	51	48	43	23

NUMBER OF LEDS	1	3	6	9	ZDC
Max Lumens	73	225	490	600	140-480
CRI	82	82	84	84	82
CBCP	313	1,140	2,761	2,577	183
CCT					

Required accessory for CE compliance: GM-XX

Model Configurator

NR					
MODEL	LUXOR CONTROL	POWER	LED COLOR	GLARE CONTROL	FINISH

LUXOR CONTROL

- ☐ **ZD** — Zone/Dim with Luxor
- ☐ **ZDC** — Zone/Dim/Color with Luxor (Large Round 3LED)

POWER

- ☐ **3LED** — 4.5 VA
- ☐ **6LED** — 9.3 VA
- ☐ **9LED** — 12.2 VA
- ☐ **[Default]** — Default ZDC Option 6.0W/7.2VA

LED COLOR

- ☐ **[Default]** — Warm (2700K)

GLARE CONTROL

- ☐ **[Default]** — Straight Cut Shroud
- ☐ **LS** — 45° Angled Long Shroud

FINISH

- ☐ **AB** Antique Bronze
- ☐ **CU** Natural Copper

Accessories

MOUNTING

- ☐  **PM-XX*** PM — Post Mount
- ☐  **GM-XX*** GM — Ground Mount with ½" Thread
- ☐  **VB-050-XX*** VB-050 — VersaBox® Mount with ½" Thread
- ☐  **MJB-050-XX*** MJB-050 — Mini J-Box for ½" Thread
- ☐  **753900** — Super Slot Spike
- ☐  **250015840000** — Long Slot Spike
- ☐  **250020020000** — Three-Prong Spike
- ☐  **VHR-UL** VHRUL — Variable Height Riser for Up Lights
- ☐  **SJ-XX*** SJ — Super J-Box Spike
- ☐  **WP-1G-050-XX*** WP-1G-050 — Single-Gang Wall Plate with ½" Thread
- ☐  **WP-RD-050-XX*** WP-RD-050 — Round Wall Plate with ½" Thread
- ☐  **GM-SS** — Gutter Mount
- ☐  **YY*-R-GT-XX*** — 1.0" (25 mm) Copper Riser for GT Path Light
- ☐  **TR-YY*-8P-XX*** TR — Tree Ring
- ☐  **PARS** — ProAim® Ratcheting Spike
- ☐  **250030410000SP** — Lock Ring

POWER



MT-6W
Plug-In Transformer, 6 W



ST-UV
Step-Down Transformer, UV (120/277 V to 12 V)



SURGE-MOD
Surge Protection Module