Runa™ RP-34 and RP-35 Path Lights



PROJECT NAME

TYPE

CATALOG #

QUANTITY

NOTES

The RP-34 and RP-35 Path Lights are made with premium copper for lasting durability against corrosion and a sleek, minimalist design for a rich, aged appearance in the landscape.

Quick Facts

- Premium, corrosion-resistant copper and brass construction protects internal and external elements of the fixture
- Extra-long, standard conduit with stabilizer enables ground mounting in any environment
- Built-in Luxor® Technology enables powerline zoning, smooth dimming, and RGBW color-changing with the Luxor Controller
- Available in static color temperature, wildlife-friendly, and dynamic RGBW color-changing options

RP-34 and RP-35 Specification Chart

Output	RP-34	RP-34	RP-35
Light Source	Powerboard™ Integrated LEDs	Powerboard™ Integrated LEDs	G4 LED Lamp
Power	1 LED	ZDC	E2
Total Lumens (lm)	40	40-45	30
Power Consumption (VA)	2.2	4.3	1.3
Efficacy (lm/W)	22	9	25
Correlated Color Temperature (CCT)	2700K (Warm) 3000K (Soft) Wildlife-Friendly (Amber)	RGBW	2700K (Warm) 3000K (Soft)
Color Rendering Index (CRI)	85+	N/A	83+
Maximum Candela (cd)	47	46	18

Input Voltage (V)	10 - 15	11 - 15	10 - 15
Luxor Compatibility			
Powerline Zoning (Z)	Default	Default	-
Smooth PWM Dimming (D)	ZD	ZD	-
RGBW Color-Changing (C)	-	ZDC	-
Minimum Rated Life (L90/B10)	72,000 Hrs	55,000 Hrs	33,000 Hrs

Technical Specifications

About FX Luminaire

As a leading manufacturer of landscape and architectural lighting, FX Luminaire provides innovative products, resources, and support to help customers bring their visions to life. The company offers a range of specification-driven solutions, including fixtures, controls, and accessories, to enhance residential and commercial landscapes.

CONSTRUCTION

Materials	Copper and brass
LED	E2
Optics	Field-serviceable lens
Threads	½"–14 NPSM with adapter
Finish	Copper/brass materials provide superior outdoor weathering in all conditions. Tested to ASTM standards. Antique finishes sealed with a clear TGIC powder-coat layer.
Hardware	Stainless steel fasteners
Wiring	18 AWG (1 mm); SPT-1W; 220°F (105°C); 300 V; 10' (3 m) length, measured from the light aperture
Sockets	Socket contains MoistureBlock™ Technology to prevent moisture from wicking up into sealed areas of the fixture
Glare Control	Full cut-off
Weight	4 lb (1.8 kg)
Ambient Operating Temperature	0°F to 140°F (-18°C to 60°C)

Lens Transparency	Frosted

SUSTAINABILITY & MANUFACTURING

Installation Requirements	Designed for installation in the downward lighting direction only
Warranty	Fixture: 10-year warranty G4 (RP-35 only): 5-year warranty

LISTINGS

Model Configurator

Options are listed per model. Not every combination of options is an orderable catalog number — confirm the configured part number against the model's SKU list before specifying.

RP34

RP34								
MODEL	LIGHTING ENGINE	LUXOR CONTROL	POWER	LED COLOR	OPTIC	COMPLIANCE	RISER	FINISH

LIGHTING ENGINE

☐	**Powerboard Integrated LED**	☐	**G4**

LUXOR CONTROL

☐	**ZD** Zone/Dim with Luxor	☐	**ZDC** Zone/Dim/Color with Luxor

POWER

☐	**[Default]** 2.2 VA, 45 lm, ZD Option Required

LED COLOR

- [ ] **[Default]** Default ZDC option 11.0 VA
- [ ] **W** Warm (2700K)
- [ ] **S** Soft (3000K)
- [ ] **T** Wildlife-Friendly (585 to 595 nm)

OPTIC

- [ ] **[Default]** NL Lamp

COMPLIANCE

- [ ] **[Default]** North America (UL Listed)
- [ ] **E** International (CE Certified)

RISER

- [ ] **18R** 18" Riser

FINISH

- [ ] **AB** Antique Bronze
- [ ] **BZ** Bronze Metallic
- [ ] **FB** Black
- [ ] **SB** Sedona Brown
- [ ] **DG** Desert Granite
- [ ] **WI** Weathered Iron
- [ ] **FW** Flat White
- [ ] **SV** Silver
- [ ] **CU** Natural Copper

RP35

RP35								
MODEL	LIGHTING ENGINE	POWER	LAMP	LED COLOR	OPTIC	COMPLIANCE	RISER	FINISH

LIGHTING ENGINE

- [ ] **Powerboard Integrated LED**
- [ ] **G4**

POWER

- [ ] **[Default]**
  2.2 VA, 45 lm, ZD Option Required

LAMP

- [ ] **E2**
  1.3 VA G4 LED Lamp (Eco Lamp Series)
- [ ] **NL**
  Lamp Not Included

LED COLOR

- [ ]  **[Default]**
  Default ZDC option 11.0 VA
- [ ] **W**
  Warm (2700K)
- [ ] **S**
  Soft (3000K)

OPTIC

- [ ] **[Default]**
  NL Lamp

COMPLIANCE

- [ ]  **[Default]**
  North America (UL Listed)

RISER

- [ ] **18R**
  18" Riser

FINISH

- [ ]  **AB**
  Antique Bronze
- [ ]  **BZ**
  Bronze Metallic
- [ ]  **FB**
  Black
- [ ]  **SB**
  Sedona Brown
- [ ]  **DG**
  Desert Granite
- [ ]  **WI**
  Weathered Iron
- [ ] **FW**
  Flat White
- [ ]  **SV**
  Silver
- [ ]  **CU**
  Natural Copper

Accessories

MOUNTING



250015840000
Long Slot Spike



250020020000
Three-Prong Spike



VHR-UL VHRUL
Variable Height Riser for Up Lights



PARS
ProAim® Ratcheting Spike



eKitSpike
CE Certified Spike



CSKIT-MPJ
Conduit Stabilizer for MP-J (with ¾” conduit)



250035490000
Adapter, ¾" Schedule 40 to ½"-14 NPSM



RP-34-DM-XX
Deck Mount for Runa RP-34 and RP-35 Path Lights



LS6054
2.5'' Post Mount with Stabilizer