Pinnacle™ PA-36 Accent Light



PROJECT NAME

TYPE

CATALOG #

QUANTITY

NOTES

Quick Facts

- Quick Facts Fully adjustable VersaBox Mount included to direct light where it's needed most, enhancing the beauty of outdoor spaces while increasing safety and visibility
- Built-in Luxor Technology enables powerline zoning, smooth PWM dimming, and RGBW color-changing control options with the industry-leading Luxor Controller
- Engineered to meet IP67 standards for added peace of mind against the elements
- 360° shield and a preinstalled hex baffle prevent glare and create an inviting atmosphere
- Durable, premium brass and copper construction offers resilience and longevity

PA-36 Spec Chart

Power	1LED	3LED	3LEDT	ZDC
Light Source	PowerBoard® Integrated LEDs	PowerBoard® Integrated LEDs	PowerBoard® Integrated LEDs	PowerBoard® Integrated LEDs
Total Lumens (lm)	115	230	115	110-260
Input Voltage (V)	10 to 15 VAC/VDC, 50/60 Hz Remote transformer required (specify separately)	10 to 15 VAC/VDC, 50/60 Hz Remote transformer required (specify separately)	10 to 15 VAC/VDC, 50/60 Hz Remote transformer required (specify separately)	10 to 15 VAC/VDC, 50/60 Hz Remote transformer required (specify separately)
Power Consumption (VA)	2.2	4.5	4.5	6.0
Correlated Color Temperature (CCT)	2700K 3000K	2700K 3000K	-	-

Efficacy (lm/W)	58	59	33	34
Color Rendering Index (CRI)	83+	83+	-	81+
Maximum Candela (cd)	272	528	-	142
Beam Angle	35°	35°	35°	35°
Luxor Compatibility				
Powerline Zoning (Z)	Default	Default	Default	Default
Smooth PWM Dimming (D)	-	ZD	ZD	ZD
RGBW Color-Changing (C)	-	-	-	ZDC
Minimum Rated Life (L70/B10)	72,000 hrs	72,000 hrs	55,000 hrs	55,000 hrs

Technical Specifications

About FX Luminaire

As a leading manufacturer of landscape and architectural lighting, FX Luminaire provides innovative products, resources, and support to help customers bring their visions to life. The company offers a range of specification-driven solutions, including fixtures, controls, and accessories, to enhance residential and commercial landscapes.

CONSTRUCTION

Materials	Brass, copper
Optics	35° beam angle lens
Threads	½"–14 NPSM
Adjustability	Compress-and-lock features prevent slips after installation. Offers 9° increments of adjustability over 220° of vertical alignment.
Finish	Options of powder-coated, natural brass finish or antiqued finish with brushed (Antique Bronze) or tumbled (Antique Tumbled) effect. Powder-coated finishes are sealed with a polyester, TGIC powder coat, providing superior outdoor weathering in all conditions. Tested to ASTM standards. Antique finishes are sealed with a clear, TGIC powder-coated layer.
Hardware	Brass and stainless-steel fasteners

Wiring	18 AWG (1 mm); SPT-1W; 220°F (105°C); 300 V; 10' (3 m) length, measured from the light aperture.
Sockets	Socket contains MoistureBlock™ Technology to prevent moisture from wicking up into sealed areas of the fixture.
Glare Control	Straight shroud, preinstalled hex baffle
Weight	1.6 lb (0.74 kg)
Ambient Operating Temperature	0°F to 140°F (-18°C to 60°C)
Lens Transparency	Clear for 1 LED/3 LED/ZD options Frosted for ZDC option

SUSTAINABILITY & MANUFACTURING

Sustainability	Innovation meets conservation in the design and manufacturing of our products. Where we can, we use recycled materials while maintaining superior functionality. Our LED products provide high quality light at optimal energy efficiency, lifespan, and durability.
Installation Requirements	Designed for installation in the upward or downward lighting directions.
Warranty	Fixture: 10-year warranty

LISTINGS

Model Configurator

PA36				
MODEL	LUXOR CONTROL	POWER	LED COLOR	FINISH

LUXOR CONTROL

- ☐ **[Default]** — On/Off | Phase Dimmable | Zone with Luxor
- ☐ **ZD** — Zone/Dim with Luxor
- ☐ **ZDC** — Zone/Dim/Color with Luxor (Round 6 LED)

POWER

- ☐ **1LED** — 2.4 VA
- ☐ **3LED** — 4.5 VA
- ☐ **[Default]** — 4.5 VA, 240 lm, ZD Option Required

LED COLOR

- ☐ **[Default]** — Default ZDC option 11.0 VA
- ☐ **W** — Warm (2700K)
- ☐ **S** — Soft (3000K)
- ☐ **T** — Wildlife-Friendly (585 to 595 nm)

FINISH

- ☐ **AB** — Antique Bronze
- ☐ **BS** — Natural Brass
- ☐ **BZ** — Bronze Metallic
- ☐ **FB** — Black
- ☐ **SB** — Sedona Brown
- ☐ **DG** — Desert Granite
- ☐ **WI** — Weathered Iron
- ☐ **FW** — Flat White
- ☐ **SV** — Silver

Accessories

MOUNTING

- ☐ **PM-XX*** PM — Post Mount
- ☐  **VB-050-XX*** VB-050 — VersaBox® Mount with ½" Thread
- ☐  **MJB-050-XX*** MJB-050 — Mini J-Box for ½" Thread
- ☐  **TB-XX*** TB — TreeBox® Mount with ½" Thread
- ☐  **250015840000** — Long Slot Spike
- ☐  **250020020000** — Three-Prong Spike



VHR-UL VHRUL
Variable Height Riser for Up Lights



SJ-XX* SJ
Super J-Box Spike



WP-1G-050-XX* WP-1G-050
Single-Gang Wall Plate with ½" Thread



WP-RD-050-XX* WP-RD-050
Round Wall Plate with ½" Thread



GM-SS
Gutter Mount



YY*-R-GT-XX*
1.0" (25 mm) Copper Riser for GT Path Light



PARS
ProAim® Ratcheting Spike



eKitSpike
CE Certified Spike



250030410000SP
Lock Ring

POWER



ST-UV
Step-Down Transformer, UV (120/277 V to 12 V)



SURGE-MOD
Surge Protection Module



ST-HV
Step-Down Transformer (120V to 12V)



ST-120-DIM
Step-Down Transformer, Dimmable (120 V to 12 V)



MT-30W
Mini Plug-In Transformer, 30 W



DIM-LV
Low-Voltage Dimmer