


## DETAIL LEGEND:

- ① FX LUMINAIRE "C-WWL" WALL WASH FIXTURE.
- ② AIM FIXTURE A MINIMUM OF 10° OFF VERTICAL TO ALLOW WATER AND DIRT TO DRAIN OFF LENS CAP.
- ③ FX LUMINAIRE LONG SLOT SPIKE
- ④ FINISHED GRADE.
- ⑤ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE 18" [46 cm] MINIMUM WIRE LOOP COILED BELOW FIXTURE FOR SERVICE.

## NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC/DC.
- C. SEE PLAN LEGEND FOR LAMP OPTION.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



C-WWL WALL WASH,  
LONG SPIKE MOUNT

**FXLuminaire.** U.C-WWL.01

NOT TO SCALE

REV: 2020-05-01