



DETAIL LEGEND:

- ① FX LUMINAIRE MP FIXTURE
- ② AIM FIXTURE A MINIMUM OF 10° OFF VERTICAL TO ALLOW WATER AND DIRT TO DRAIN OFF LENS CAP
- ③ FX LUMINAIRE BRASS TOP CAP MOUNTED ON FX CDS STAKE
- ④ FINISHED GRADE
- ⑤ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED BEHIND FIXTURE FOR FUTURE SERVICE.
- ⑥ HEAT SHRINK WIRE CONNECTORS

NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC OR DC
- C. SEE PLAN LEGEND FOR LED BOARD OPTION, BEAM SPREADS, AND ACCESSORIES.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



UP LIGHT (MP) - SUPER J-BOX MOUNT

FXLuminaire. U.MP.03

NOT TO SCALE
REV: 2022-02-04