


DETAIL LEGEND:

- ① FX LUMINAIRE MP FIXTURE
- ② AIM FIXTURE A MINIMUM OF 10° OFF VERTICAL TO ALLOW WATER AND DIRT TO DRAIN OFF LENS CAP
- ③ FX LUMINAIRE POST MOUNT GROUND STAKE. SEE PLAN FOR TOP COLOR.
- ④ CAP 1/4" - 1/2" [6mm-13mm] ABOVE GRADE
- ⑤ FINISHED GRADE
- ⑥ USE CUSTOM SIZE PIPE SUPPLIED BY FX LUMINAIRE OR 1.5" NOM SCHEDULE 40 PVC
- ⑦ DIRECT BURY, UF/UL, COPPER, LOW VOLTAGE CABLE WITH UL 486D (IEC/EN 60998) RATED WATERPROOF CONNECTION. LEAVE MINIMUM WIRE LOOP COILED BEHIND FIXTURE FOR FUTURE SERVICE.
- ⑧ HEAT SHRINK WIRE CONNECTORS

NOTES

- A. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- B. ACCEPTS 10-15 VOLTS - AC OR DC
- C. SEE PLAN LEGEND FOR LED BOARD OPTION, BEAM SPREADS, AND ACCESSORIES.
- D. ALWAYS REFER TO FX PRODUCT INSTALLATION NOTES PRIOR TO INSTALLATION.



XX UP LIGHT (MP) - POST MOUNT
FXLuminaire. U.MP.02

NOT TO SCALE
REV: 2022-02-04